

CAMERA LEASH KIT

CLK

For iako-mounted cameras

WHAT'S INCLUDED

- 1x Velcro strap with D-ring
- 1x D-ring positioning pad (velcro)
- 1x High-strength leash loop (pre-tied)

WHAT YOU'LL NEED

- Your installed iako camera mount
- Your camera with leash mount or finger grip

INSTALLATION

Inspect the velcro strap and leash loop before every paddle. Do not use if either shows wear or damage.

1. Wrap the velcro strap around the iako and secure it to itself. Position it close to your camera mount.
2. Place the D-ring positioning pad on the iako at your preferred location and press firmly against the surface — this protects the iako and keeps the D-ring from sliding.
3. To attach to your camera's leash mount: feed one end of the leash loop through the leash mount, then pass the entire tether assembly (D-ring and velcro strap) through the loop and pull snug. This creates a secure girth hitch that cannot pull free. Alternatively, loop directly around the finger grip.
4. Give the tether a firm tug to confirm the girth hitch is seated before launching.

⚠ IMPORTANT

1. Always route the velcro strap through the D-ring — never rely on the positioning pad alone to secure your camera.
2. This kit reduces the risk of camera loss — it does not eliminate it. No leash system is a guarantee.

CARE

Rinse with fresh water after saltwater use. Velcro collects debris over time — clean regularly to maintain grip strength.

DISCLAIMER

By purchasing and using this product, the user assumes all risk associated with its installation and use. SEAT6 is not liable for loss of or damage to any property, equipment, or persons resulting from improper installation, overloading, misuse, or use outside these instructions.

Questions? hello@seat6.shop

